



MICROWELL

European manufacturer of swimming pool dehumidifiers, heat pumps and germicidal air purifiers.



2025 PRICE LIST

Swimming pool HEATING &
DEHUMIDIFICATION solutions
UV Air Disinfection systems

Valid from: FEBRUARY 13, 2025

WHY MICROWELL?

VARIETY OF MODELS
 WIDEST RANGE OF DESIGN AND ACCESSORIES
 EXCELLENT CRAFTSMANSHIP AND EXPERIENCE
 INNOVATIVE ENGINEERING, CUTTING EDGE ROBOTICS
 EUROPEAN QUALITY, LOCATED IN SLOVAKIA
 750+ PARTNERS IN 40+ COUNTRIES
 COMPETITIVE PRICES
 ACCREDITED BY ISO 9001, ISO 14001, ISO 45001



Dear Business Partners,

With great respect and gratitude, let us introduce our new Pricelist which is not only a showcase of our products, but also a reflection of our long-term efforts and determination to bring our customers the best solutions.

Our company Microwell has been operating on the market for more than 25 years, during which we have tried not only to keep up with technological developments, but also to exceed the expectations of you, our customers. This journey would not have been possible without your continued support and loyalty.

For many, the year 2024 was marked as a year full of challenges, unfortunately accompanied by some unfavorable economic and geopolitical factors. The ongoing conflict between Russia and Ukraine, economic and political instability of EU, significant inflation, etc. affected both global and local markets. Despite these difficult conditions, we at Microwell did not hesitate and continued to fulfill our vision, which is to bring top technological solutions to our customers.

In 2024, we reached an important milestone in the field of technology and innovation. We have built a specialized test chamber that enables thorough testing and improvement of our products. Even in this difficult time, we have successfully implemented a number of projects focused on technical-technological development and product design enhancement. This has resulted in several innovations listed in our product portfolio. In the field of pool dehumidifiers, we have introduced several important novelties such as SoundSteel technology/Improved noise reduction thanks to the double silent block, new generation of controllers, PV ready solution, new aluminum covers, DRY Orient design - Wi-fi and RS 485-485 (Modbus) option for DRY products for easier monitoring and management system.

Our next significant step was the introduction of a new line of HP SILVER Inverter Pro year-round swimming pool heat pumps. These products stand out not only for their technological excellence, but also for their attractive design, that meets the highest expectations of our customers.


A look into the future

The year 2024 reminded us that even in uncertain times it is possible to grow, innovate and push the boundaries of what is possible. Our path is not easy, but thanks to the determination of our team and trust of our partners, we believe that a successful and promising future awaits us. Together, we will continue to deliver innovative solutions that improve lives and move our industry forward.

Sincerely,



Ing. Tibor Kovács, CEO



MICROWELL Headquarters

Microwell operates in 3 business divisions /Dehumidification, Heating and UV Air Disinfection Solutions, Measurement and Control, Air conditioning and Ventilation/, employs 70 employees in 5 Branch offices in 3 countries: Slovakia, Czech Republic, Hungary/. The company has own manufacturing facilities, warehouse, R&D department.



The core strength of Dehumidification, Heating and UV Air Disinfection Solutions Division is its R&D team, that works hard, permanently focused on customers needs, to find new solutions and innovations.



Production & warehouse

Primary manufacturing facility located in 3.000m² venue. Office extends over 1.260m².



NEW OFFICE





Germicidal Air Purifiers Pages 6 - 9

ATHMOSS germicidal air purifier

ATHMOSS 120 OFFICE
ATHMOSS 120 INDUSTRY
ATHMOSSphere

8-9



Dehumidifiers

Pages 10 - 35

SWIMMING POOL DEHUMIDIFIERS on the wall, on the floor, behind the wall

DRY 300 WAVE		
DRY 300 METAL / ALU	30m ² /36l	14-15
DRY 300 SILVER		
DRY 400 WAVE		
DRY 400 METAL / ALU	45m ² /48l	16-17
DRY 400 SILVER		
DRY 500 WAVE		
DRY 500 METAL / ALU	60m ² /66l	20-21
DRY 500 SILVER		
DRY 800 WAVE		22
DRY 1200 WAVE	90-120m ² /90-120l	
DRY 800 METAL / ORIENT		23
DRY 1200 METAL / ORIENT		24
DRY SALT+ SULPHUR+		

SWIMMING POOL DEHUMIDIFIERS ducted

DRY 300 DUCT		
DRY 400 DUCT		
DRY 500 DUCT		
DRY 800 DUCT		26-29
DRY 1200 DUCT		

SWIMMING POOL DEHUMIDIFIERS ceiling mounted

SIREN ECO MONO	60-120m ² /67-134l	30
SIREN ECO DUE		32
DRY HORIZON		

DEHUMIDIFIERS FOR GALLERIES

DRY GALLERY		34
-------------	--	----

DEHUMIDIFIERS FOR INDUSTRY

T40 T90 T120		35
TE40 TE90 TE120		



Heat pumps

Pages 36 - 59

SWIMMING POOL HEAT PUMPS ON/OFF /up to 120 m³/

HP 2300 INVENTOR	23-28kW/80-120m ³	42-43
HP 2800 INVENTOR		

SWIMMING POOL HEAT PUMPS SEASONAL INVERTER /up to 50 m³/

HP 900 BLACK	9kW/30m ³	46
HP 1100 BLACK	11.5kW/35m ³	46
HP 1500 BLACK	15kW/50m ³	47

SWIMMING POOL HEAT PUMPS FULL YEAR INVERTER /up to 135 m³/

HP 1100 SILVER Inverter Pro	11kW/40m ³	48
HP 1500 SILVER Inverter Pro	15kW/60m ³	49
HP 1800 SILVER Inverter Pro	18kW/95m ³	50
HP 2100 SILVER Inverter Pro	21kW/105m ³	51
HP 2800 SILVER Inverter Pro	28kW/135m ³	52

SWIMMING POOL HEAT PUMPS FULL YEAR PREMIUM /up to 120 m³/

HP 2400 PREMIUM	24kW/80m ³	
HP 3000 PREMIUM	30kW/120m ³	54-55

COMMERCIAL SWIMMING POOL HEAT PUMPS INVERTER /up to 520 m³/

MAX 50 - 450	50-450kW/260-520m ³	56
iMAX 50-450		



Accessories & Spare parts

Pages 60 - 75

QMAX-HEAT PUMP TESTER		61
HUMIDITY VISUALIZATION microLIGHT+		63
INSTALLATION MATERIAL AND EQUIPMENT FOR INSTALLATION AND SERVICE		65
WATER SURFACE COVER		73
VENTILATION		74

NEW IN 2025

SILVER INVERTER PRO

The Silver Inverter Pro brings year-round heating and cooling with capacities of 11, 15, 17, 21, and 28 kW in monoblock and split configurations. Its advanced airflow system ensures quiet, efficient performance, while prototypes with R290 (Propane) lead the way to a greener future.

Experience efficiency and sustainability with the Silver Inverter Pro.

Full model line read on **pages 48-52.**

SILVER INVERTER PRO



NEW IN 2025

NEW CONTROLLER



NEW CONTROLLER

Our new smart controller combines advanced technology with user-friendly features. It includes a sleek touchscreen display, built-in Wi-Fi for seamless smart home integration, and RS-485 connectivity for Modbus communication. Fully customizable, it allows precise control of drying, fan management, and other accessories, making it an ideal solution for modern automation needs. Designed for efficiency and versatility, it's the perfect upgrade for Microwell dehumidifiers.

DRY ALU


All Microwell Dry 300, 400, and 500 dehumidifiers will feature aluminum covers, replacing steel. This upgrade offers:

- Higher Corrosion Resistance: Ideal for pool environments.
- Lighter Weight: Easier transport and installation.
- Improved Ventilation Design: Enhanced air circulation for optimal performance.

Experience the next level of durability and efficiency with our upgraded dehumidifiers.

Full model line read on **pages 15-21.**

ALUMINIUM COVER



ATHMOSS  **ATHMOSSphere**

The essential presence of the future.



Germicidal air purifiers

For offices, waiting rooms, retirement houses, event, fitness and shopping centers.

For industry premises, production halls.

**Professional, powerful
Air purifier & Disinfector
safe to use at presence of people**

Destroys viruses, bacteria and other microorganisms in the air.

The ATHMOSS germicidal air purifier will create a safe and healthy environment in your office, production hall or doctor's waiting room.



Series	ATHMOSS 120	ATHMOSS 120	ATHMOSSphere
Model	OFFICE	INDUSTRY	
Installation	wall mounted/on the floor with mobile stand		ceiling mounted
Recommended size of disinfected area	15-450 m ³	25-600 m ³	100-1000 m ³
Dimensions /WxHxD/	770 x 660 x 260 mm		Ø 1210 x 278 mm
Weight	20.5 kg	21.5 kg	
Cover	Acrylic, white		Acrylic, white
Noise level	33.5 dB(A) MIN 45.8 dB(A) MAX	39.1 dB(A) MIN 58.2 dB(A) MAX	34 dB(A) MIN 62 dB(A) MAX
Air flow	50-495 m ³ /h, adjustable	50-700 m ³ /h, adjustable	400-800 m ³ /h, adjustable
Power supply	230V AC/50Hz/1ph		230V AC/50Hz/1ph
Consumption	95-100-152 W	188-237 W	270-380 W
Number and performance of UV-C tubes	6 x 15 W /253.7 nm UV-C/		12 x 15 W /253.7 nm UV-C/
Operating life-time of UV-C tubes	<9000h		<9000h
Prefilter	Class G3 >10µm		Class G3 >10µm
HEPA filter	Class H11 >0.3µm, 95%		Class H11 >0.3µm, 95%



Manufacturer notice: Manufacturer reserves the right to change the technical parameters without notice.

Tested and confirmed by the Institute of Clinical Microbiology, Faculty of Medicine UK in Hradec Králové, Czech Republic.



Effect of the air purifier ATHMOSS INDUSTRY 120 on artificial contaminated laboratory air pollution of bacteria - 47m³

Effect of the air purifier ATHMOSSphere on artificial contaminated laboratory air pollution of bacteria - 126m³



90W
495 m³**ATHMOSS 120 OFFICE***Quiet, yet effective.*90W
700 m³**ATHMOSS 120 INDUSTRY***Powerful without compromise.*

Cover	Acrylic, white	
UV-C tubes	6x15W /253,7 nm/	
Air flow	50-495 m ³ /h	50-700 m ³ /h
Prefilter	Class G3 >10 µm	
HEPA filter	Class H11 >0,3 µm, 95%	
microMETAL+ stainless steel filter		
Installation	Wall mounted	

ATHMOSS **ATHMOSS 120 O** - **1.****ATHMOSS 120 I** - **1.**


Basic equipment:	Model:	Price EXW Sala, SK w/o VAT
Germicidal air purifier, wall console, 90W UV-C <9.000hrs, G3 prefilter, H11 95% HEPA filter, microMETAL+ stainless steel filter, user's manual	ATHMOSS 120 OFFICE	1 980 €
	ATHMOSS 120 INDUSTRY	2 150 €

1. Installation:

S Standard: on the wall	0 €
M Mobile stand (vertically adjustable 145-185cm), RAL9010 white, 4 wheels (2 lockable): <i>/Rebate does not apply on this item. This is the actual purchase price./</i>	115 €
P Through-the-wall installation (Fiberglass cover with through-the-wall ducts set and removable aluminium grills, metal duct galvanized, wall thickness >400mm, insulated)	385 €

**1-M**

Spare parts:	Price EXW Sala, SK w/o VAT
Spare Disinfection chamber with 90W UV-C, with microMETAL+ stainless steel filter and HEPA filter H11	760 €
HEPA filter H11, 1pc, >0.3µm, 95% <i>/Rebate does not apply on this item. This is the actual purchase price./</i>	15 €
Pre-filter class G3, package of 3pcs, >10µm <i>/Rebate does not apply on this item. This is the actual purchase price./</i>	9 €

**1-P**EURO PALETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)


180W
495 m³

ATHMOSSphere

The essential presence of the future.

ATHMOSSphere

Cover	Acrylic, white
UV-C tubes	12x15W /253,7 nm/
Air flow	400-800 m ³ /h adjustable
Prefilter	Class G3 >10 µm
HEPA filter	Class H11 >0,3 µm, 95%
microMETAL+ stainless steel filter	
Installation	Ceiling mounted



GERMICIDAL AIR PURIFIER

ATHMOSSphere

Basic equipment: Price EXW Sala, SK w/o VAT

Ceiling germicidal air purifier, 180W UV-C <9.000hrs, G3 prefilter, H11 95% HEPA filter, microMETAL+ stainless steel filter, ceiling lifting mechanism, user's manual

3 150 €

Spare parts: Price EXW Sala, SK w/o VAT

Spare Disinfection chamber with 180W UV-C, with microMETAL+ stainless steel filter and HEPA filter H11

1 250 €

HEPA filter H11, 1pc, >0.3µm, 95%
/Rebate does not apply on this item. This is the actual purchase price./


15 €

Pre-filter class G3, package of 3pcs, >10µm
/Rebate does not apply on this item. This is the actual purchase price./

9 €



EURO PALETTE packed, FUMIGATED
17.50€/1pc
(Depending on the model it is possible to pack more units on EUP (2-6pcs).)



v. 01/2025

 **MICROWELL**



Dehumidifiers

For swimming pools, hotel pools, spa and jacuzzi
For galleries, museums and libraries
For industry

LIFETIME
WARRANTY ON
CONDENSING TRAY

5 YEAR
WARRANTY ON
COMPRESSOR




























3 YEAR
GENERAL
WARRANTY ON
SPARE PARTS

Swimming pool humidity under control

Microwell dehumidifiers solve humidity problems and maintain healthy pool environment by removing condensation and wet wall odour, and providing free heating through heat recovery.

Working on the principle of condensation, DRY swimming pool dehumidifiers are removing humid air from swimming pool hall, replacing it with dry and warm air.


MICROWELL DRY Line 2025

		Pool surface	Extraction rate	Extraction rate	Air flow	Noise level (at 1m distance)	Power consumption	Heating output	Dimensions netto	Weight netto
	Model	m ²	l/24hrs /60% RH, 30°C/	l/24hrs /80% RH, 30°C/	m ³ /h	dB(A)	W	W	mm	kg
Economy class - WAVE	 DRY 300 WAVE	30	36	48	550	42	700	1900	780 x 660 x 255	40
	 DRY 400 WAVE	45	48	58	600	42	700	1900	780 x 660 x 255	40
	 DRY 500 WAVE	60	66	101	800	44	1000	3500	1245 x 660 x 255	60
	 DRY 800 WAVE	90	90	136	1100	46	1600	5100	1250 x 950 x 310	80
	 DRY 1200 WAVE	120	120	181	1200	46	2150	5250	1250 x 950 x 310	82
Premium class - METAL/ALUMINIUM	 DRY 300 METAL / ALU	30	36	48	550	42	700	1900	780 x 642 x 300	43
	 DRY 400 METAL / ALU	45	48	58	600	42	700	1900	780 x 642 x 300	43
	 DRY 500 METAL / ALU	60	66	101	800	44	1000	3500	1245 x 642 x 300	65
	 DRY 800 METAL	90	90	136	1100	46	1600	5100	1250 x 950 x 310	100
	 DRY 1200 METAL	120	120	181	1200	46	2150	5250	1250 x 950 x 310	101
LUXURY class - STAINLESS STEEL	 DRY 300 SILVER	30	36	48	550	42	700	1900	780 x 642 x 300	50
	 DRY 400 SILVER	45	48	58	600	42	700	1900	780 x 642 x 300	50
	 DRY 500 SILVER	60	66	101	800	44	1000	3500	1245 x 642 x 300	77
Through-the-wall - Concealed	 DRY 300 TTW	30	36	48	550	42	700	1900	880 x 658 x 240	56
	 DRY 400 TTW	45	48	58	600	42	700	1900	880 x 658 x 240	56
	 DRY 500 TTW	60	66	101	800	44	1000	3500	1245 x 660 x 255	60
	 DRY 800 TTW	90	90	136	1100	46	1600	5100	1247 x 950 x 300	100
	 DRY 1200 TTW	120	120	181	1200	46	2150	5250	1247 x 950 x 300	103
Ducted - To air ducting	 DRY 300 DUCT	30	32	43	500/200Pa	54	800	1900	880 x 658 x 240	56
	 DRY 400 DUCT	40	43	56	500/200Pa	54	800	1900	880 x 658 x 240	56
	 DRY 500 DUCT	50	52	68	1000/200Pa	56	1150	3500	1250 x 660 x 250	78
	 DRY 800 DUCT	80	88	135	1100/170Pa	58	1700	5100	1247 x 950 x 300	102
	 DRY 1200 DUCT	110	112	170	1200/145Pa	60	2250	5250	1247 x 950 x 300	103
Ceiling	 DRY HORIZON 800	90	94	141	1150	58	2000	5100	1083 x 742 x 540	102
	 DRY HORIZON 1200	120	127	194	1800	64	2300	5300	1083 x 742 x 540	108
	 SIREN Eco MONO	60	67	104	1000	35	1000	4500	Ø 1210 x 278	53+20
	 SIREN Eco DUE	120	134	208	2000	35	2300	8750	2x Ø 1210x 278	2x53+30


The manufacturer reserves the right to change the parameters without notice.



REIMAGINED, REDESIGNED, REINVIGORATED



2025 NEW DESIGN



Microwell DRY Series swimming pool dehumidifiers come equipped with these features as standard:

- Touch digital controller
- WiFi
- Self-diagnosis
- RS-485 (ModBus)
- Passive defrosting - function available from +9°C
- Full functionality for all other accessories (heating, boiler control, PV ready, DRY contact, etc.), which can also be used after the device is installed
- For METAL/ALU models, the casing is made of aluminum (previously steel) - lower weight and higher corrosion resistance
- Double silent block for the compressor + additional noise reduction using SoundSteel material


LIGHTER THAN EVER



36 l
30 m²

DRY 300 WAVE

Cover	Extraction rate (30°C/60% RH - 35°C/95% RH)	Air flow
plastic (acryl)	36-63 l/24hrs	550 m ³ /hour



DRY 300W - 1. - 2. - 3. - 4. - 5. - 6. - 7. - 8.

Basic equipment: **Price EXW**
w/o VAT /EUR/

Dehumidifier, wall console, user's manual, installation layout, fixation screws

micro COMPRESSOR+ ultra QUIET+ easy INSTALL+



2 890

1. Installation:

S standard: on the wall	0
M mobile stand, 4 wheels, white color (RAL 9010), 230V EURO plug, 2m	235
F fixed floor stand, color: white RAL9010 - matching the color of the main unit, 230V EURO plug, 2m	260
P through-the-wall INDOOR INSTALLATION (fiberglass cover with TTW ducts set and removable aluminum grills, metal ducts galvanized, insulated)	595
T Premium through-the-wall INDOOR INSTALLATION (metal powder coated cover, wall ducts, removable grills, metal ducts galvanized, insulated)	1 390
E through-the-wall OUTDOOR INSTALLATION (40mm TTW external aluminum and rubber insulation, winter module, condensate tray defrost, -15°C), fiberglass cover	1 350

2. Control:

S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)	0
E remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)	345
W6 remote wired humidistat EBERLE HYG6001+built-in touch controller	120
W7 remote wired humidistat & thermostat EBERLE HYG7001+built-in touch controller	140

3. Air temperature:

S standard: +9°C...+36°C	0
V +9°C...+42°C (high temperature set)	259
F +5°C...+35°C (low temperature set with 4-way valve hot gas defrost)	385

4. Air heating:

S standard: without LPHW (Low Pressure Hot Water)	0
H LPHW, 3.5 kW, without regulation	228
V LPHW, 3.5 kW, with solenoid valve, fully automated regulation	442
E Electrical heating 2 kW	490

5. LPHW connection:

S standard: N/A (without LPHW)	0
B from the back	0
R from right	0
L from left	0

6. micro LIGHT+

S standard: without Pool Security microLIGHT+	0
L Pool Security microLIGHT+	140

7. Air filter:

S standard: without air filter	0
F Air filter (for model with wall or mobile stand installation: 1-S/M/F option)	52
C Air filter grid (for model with TTW installation: 1-P/E option) (G3 class)	52

8. Fresh air supply:

S standard: without fresh air supply	0
F adapter, Ø 100 mm, 50 mm length, galvanized	35



EURO PALETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)


36 l
30 m²

DRY 300 METAL / ALU | DRY 300 SILVER

Cover	Cover	Extraction rate	Air flow
DRY 300 METAL / ALU	DRY 300 SILVER	(30°C/60% RH - 35°C/95% RH)	
aluminium	stainless steel	36-63 l/24hrs	550 m ³ /hour



DRY 300M



DRY 300S

SWIMMING POOL DEHUMIDIFIERS

DRY 300M - 1. - 2. - 3. - 4. - 5. - 6. - 7. - 8. - 9.


DRY 300S - - 2. - 3. - 4. - 5. - 6. - 7. - 8. - 9.



Wi-Fi included

100% corrosion free

Basic equipment:	Model:	Price EXW w/o VAT /EUR/
Dehumidifier, wall console, user's manual installation layout, fixation screws	DRY 300 METAL / ALU	3 380
micro COMPRESSOR+ ultra QUIET+ easy INSTALL+	DRY 300 SILVER	4 370
FREE 3 YEARS WARRANTY		
1. Color options:		
W standard: white (RAL9010)		0
S silver color ,Silver grey' - Tiger		85
C color selection according to your preference (RAL code) - 200+ colors		price on demand
2. Installation:		
S standard: on the wall		0
M mobile stand, 4 wheels, color: silver 'Tiger', white (RAL 9010), 230V EURO plug, 2m		235
F fixed floor stand, color: black RAL9005, 230V EURO plug, 2m		260
3. Control:		
S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)		0
E remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)		345
W6 remote wired humidistat EBERLE HYG6001+built-in touch controller		120
W7 remote wired humidistat & thermostat EBERLE HYG7001+built-in touch controller		140
4. Air temperature:		
S standard: +9°C...+36°C		0
V +9°C...+42°C (high temperature set)		259
F +5°C...+35°C (low temperature set with 4-way valve hot gas defrost)		385
5. Air heating:		
S standard: without LPHW (Low Pressure Hot Water)		0
H LPHW, 3.5 kW, without regulation (external no current contact)		228
V LPHW, 3.5 kW, fully automatic regulation (with solenoid valve + external no current contact)		442
E Electrical heating 2 kW		490
6. LPHW connection:		
S standard: N/A (without LPHW)		0
B from the back		0
R from right		0
L from left		0
7. micro LIGHT+		
S standard: without Pool Security microLIGHT+		0
L Pool Security microLIGHT+		140
8. Air filter:		
S standard: without air filter		0
F Air filter		52
9. Fresh air supply:		
S standard: without fresh air supply		0
F adapter, Ø 100 mm, 50 mm length, galvanized		35



EURO PALLETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)




v. 01/2025



48 l
45 m²

DRY 400 WAVE

Cover	Extraction rate (30°C/60% RH - 35°C/95% RH)	Air flow
plastic (acryl)	48-78 l/24hrs	600 m ³ /hour



DRY 400W - 1. - 2. - 3. - 4. - 5. - 6. - 7. - 8.

Basic equipment:

Price EXW
w/o VAT /EUR/

Dehumidifier, wall console, user's manual, installation layout, fixation screws

micro COMPRESSOR+ ultra QUIET+ easy INSTALL+



3 330

1. Installation:

S standard: on the wall	0
M mobile stand, 4 wheels, white color (RAL 9010), 230V EURO plug, 2m	235
F fixed floor stand, color: white RAL9010 - matching the color of the main unit, 230V EURO plug, 2m	260
P through-the-wall INDOOR INSTALLATION (fiberglass cover with TTW ducts set and removable aluminum grills, metal ducts galvanized, insulated)	595
T Premium through-the-wall INDOOR INSTALLATION (metal powder coated cover, wall ducts, removable grills, metal ducts galvanized, insulated)	1 390
E through-the-wall OUTDOOR INSTALLATION (40mm TTW external aluminum and rubber insulation, winter module, condensate tray defrost, -15°C), fiberglass cover	1 350

2. Control:

S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)	0
E remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)	345
W6 remote wired humidistat EBERLE HYG6001+built-in touch controller	120
W7 remote wired humidistat & thermostat EBERLE HYG7001+built-in touch controller	140

3. Air temperature:

S standard: +9°C...+42°C	0
---------------------------------	---

4. Air heating:

S standard: without LPHW (Low Pressure Hot Water)	0
H LPHW, 3.5 kW, without regulation	228
V LPHW, 3.5 kW, with solenoid valve, fully automated regulation	442
E Electrical heating 2 kW	490

5. LPHW connection:

S standard: N/A (without LPHW)	0
B from the back	0
R from right	0
L from left	0

6. micro LIGHT+


S standard: without Pool Security microLIGHT+	0
L Pool Security microLIGHT+	140

7. Air filter:

S standard: without air filter	0
F Air filter (for model with wall or mobile stand installation: 1-S/M/F option)	52
C Air filter grid (for model with TTW installation: 1-P/E option) (G3 class)	52

8. Fresh air supply:

S standard: without fresh air supply	0
F adapter, Ø 100 mm, 50 mm length, galvanized	35




EURO PALETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)


48 l
45 m²

DRY 400 METAL / ALU | DRY 400 SILVER

Cover	Cover	Extraction rate	Air flow
DRY 400 METAL / ALU	DRY 400 SILVER	(30°C/60% RH - 30°C/80% RH)	
aluminium	stainless steel	48-78 l/24hrs	600 m ³ /hour



DRY 400M



DRY 400S

DRY 400M - 1. - 2. - 3. - 4. - 5. - 6. - 7. - 8. - 9.

DRY 400S - - 2. - 3. - 4. - 5. - 6. - 7. - 8. - 9.



Wi-Fi included

100% corrosion free

SWIMMING POOL DEHUMIDIFIERS

Basic equipment:	Model:	Price EXW w/o VAT / EUR/
Dehumidifier, wall console, user's manual installation layout, fixation screws	DRY 400 METAL / ALU	3 830
micro COMPRESSOR+ ultra QUIET+ easy INSTALL+ FREE 3 YEARS WARRANTY	DRY 400 SILVER	4 850
1. Color options:		
W standard: white (RAL9010)		0
S silver color ‚Silver grey‘ - Tiger		85
C color selection according to your preference (RAL code) - 200+ colors		price on demand
2. Installation:		
S standard: on the wall		0
M mobile stand, 4 wheels, color: silver ‚Tiger‘, white (RAL 9010), 230V EURO plug, 2m		235
F fixed floor stand, color: black RAL9005, 230V EURO plug, 2m		260
3. Control:		
S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)		0
E remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)		345
W6 remote wired humidistat EBERLE HYG6001+built-in touch controller		120
W7 remote wired humidistat & thermostat EBERLE HYG7001+built-in touch controller		140
4. Air temperature:		
S standard: +9°C...+36°C		0
5. Air heating:		
S standard: without LPHW (Low Pressure Hot Water)		0
H LPHW, 3.5 kW, without regulation		228
V LPHW, 3.5 kW, with solenoid valve, fully automated regulation		442
E Electrical heating 2 kW		490
6. LPHW connection:		
S standard: N/A (without LPHW)		0
B from the back		0
R from right		0
L from left		0
7. microLIGHT+		
S standard: without Pool Security microLIGHT+		0
L Pool Security microLIGHT+		140
8. Air filter:		
S standard: without air filter		0
F Air filter		52
9. Fresh air supply:		
S standard: without fresh air supply		0
F adapter, Ø 100 mm, 50 mm length, galvanized		35



EURO PALLETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)



v. 01/2025

MICROWELL

Dehumidification, ventilation and heating with one device

- Dehumidify
- Heat
- Fresh air, Ventilation

3 in 1



MICROWELL

LEADING EUROPEAN SWIMMING POOL DEHUMIDIFIERS MANUFACTURER

www.microwell.eu

Customized solution

Microwell provides tailored on-demand service for individual solutions for general prices similar to those of serial production

- Demand your tailor made solution & design by Microwell
- Select from 25 basic models
- Add from 50+ available accessories
- Create right-to-fit unit for your needs

If you did not find what you expected elsewhere, we may have a solution.



66 l
60 m²


DRY 500 WAVE

Cover	Extraction rate (30°C/60% RH - 35°C/95% RH)	Air flow
plastic (acryl)	66-132 l/24hrs	800 m ³ /hour



DRY 500W - 1. - 2. - 3. - 4. - 5. - 6. - 7. - 8.

Basic equipment:		Price EXW w/o VAT /EUR/
Dehumidifier, wall console, user's manual, installation layout, fixation screws		4 090
micro COMPRESSOR+ ultra QUIET+ easy INSTALL+		
1. Installation:		
S	standard: on the wall	0
M	mobile stand, 4 wheels, white color (RAL 9010), 230V EURO plug, 2m	265
F	fixed floor stand, color: white RAL9010 - matching the color of the main unit, 230V EURO plug, 2m	280
P	through-the-wall INDOOR INSTALLATION (fiberglass cover with TTW ducts set and removable aluminum grills, metal ducts galvanized, insulated)	740
T	Premium through-the-wall INDOOR INSTALLATION (metal powder coated cover, wall ducts, removable grills, metal ducts galvanized, insulated)	1 590
E	through-the-wall OUTDOOR INSTALLATION (40mm TTW external aluminum and rubber insulation, winter module, condensate tray defrost, -15°C), fiberglass cover	1 480
2. Control:		
S	standard: built-in digital touch controller with WiFi and RS-485 (Modbus)	0
E	remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)	345
W6	remote wired humidistat EBERLE HYG6001+built-in touch controller	120
W7	remote wired humidistat & thermostat EBERLE HYG7001+built-in touch controller	140
3. Air temperature:		
S	standard: +9°C...+36°C	0
V	+9°C...+42°C (high temperature set)	259
F	+5°C...+35°C (low temperature set with 4-way valve hot gas defrost)	385
4. Air heating:		
S	standard: without LPHW (Low Pressure Hot Water)	0
H	LPHW, 5 kW, without regulation	228
V	LPHW, 5 kW, with solenoid valve, fully automated regulation	442
E	Electrical heating 2 kW	490
5. LPHW connection:		
S	standard: N/A (without LPHW)	0
B	from the back	0
R	from right	0
L	from left	0
6. microLIGHT+		
S	standard: without Pool Security microLIGHT+	0
L	Pool Security microLIGHT+	140
7. Air filter:		
S	standard: without air filter	0
F	Air filter (for model with wall or mobile stand installation: 1-S/M/F option)	54
C	Air filter grid (for model with TTW installation: 1-P/E option) (G3 class)	67
8. Fresh air supply:		
S	standard: without fresh air supply	0
F	adapter, Ø 100 mm, 50 mm length, galvanized	35



EURO PALETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)

66 l
60 m²

DRY 500 METAL / ALU | DRY 500 SILVER

Cover	Cover	Extraction rate	Air flow
DRY 500 METAL / ALU	DRY 500 SILVER	(30°C/60% RH - 35°C/95% RH)	
aluminium	stainless steel	66-132 l/24hrs	800 m ³ /hour



DRY 500M



DRY 500S

SWIMMING POOL DEHUMIDIFIERS

DRY 500M - 1. - 2. - 3. - 4. - 5. - 6. - 7. - 8. - 9.

DRY 500S - 1. - 2. - 3. - 4. - 5. - 6. - 7. - 8. - 9.



100%
corrosion free

Basic equipment:	Model:	Price EXW w/o VAT /EUR/
Dehumidifier, wall console, user's manual, installation layout, fixation screws	DRY 500 METAL / ALU	4 870
micro COMPRESSOR+ ultra QUIET+ easy INSTALL+ FREE 3 YEARS WARRANTY	DRY 500 SILVER	6 200

1. Color options:		
W standard: white (RAL9010)		0
S silver color „Silver grey“ - Tiger		100
C color selection according to your preference (RAL code) - 200+ colors		price on demand

2. Installation:		
S standard: on the wall		0
M mobile stand, 4 wheels, color: silver 'Tiger', white (RAL 9010), 230V EURO plug, 2m		265
F fixed floor stand, color: black RAL9005, 230V EURO plug, 2m		280

3. Control:		
S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)		0
E remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)		345
W6 remote wired humidistat EBERLE HYG6001+built-in touch controller		120
W7 remote wired humidistat & thermostat EBERLE HYG7001+built-in touch controller		140

4. Air temperature:		
S standard: +9°C...+35°C		0
V +9°C...+42°C (high temperature set)		259
F +5°C...+35°C (low temperature set with 4-way valve hot gas defrost)		385


5. Air heating:		
S standard: without LPHW (Low Pressure Hot Water)		0
H LPHW, 5 kW, without regulation		246
V LPHW, 5 kW, with solenoid valve, fully automated regulation		458
E Electrical heating 2 kW		490

6. LPHW connection:		
S standard: N/A (without LPHW)		0
B from the back		0
R from right		0
L from left		0

7. micro LIGHT+		
S standard: without Pool Security microLIGHT+		0
L Pool Security microLIGHT+		140

8. Air filter:		
S standard: without air filter		0
F Air filter		54

9. Fresh air supply:		
S standard: without fresh air supply		0
F adapter, Ø 100 mm, 50 mm length, galvanized		35



EURO PALLETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)



v. 01/2025



90l
90 m²

DRY 800 WAVE


120l
120 m²

DRY 1200 WAVE

Cover	Extraction rate (30°C/60% RH - 35°C/95% RH)	Air flow	Extraction rate (30°C/60% RH - 35°C/95% RH)	Air flow
plastic (acryl) white color	90-180 l/24hrs	1100 m ³ /hour	120-240 l/24hrs	1200 m ³ /hour

DRY 800W - 1. - 2. - 3. - 4. - 5. - 6. - 7. - 8.

DRY 1200W - 1. - 2. - 3. - 4. - 5. - 6. - 7. - 8.



Basic equipment:

Model:

Price EXW
w/o VAT /EUR/

Dehumidifier, floor feet, user's manual

DRY 800 WAVE

5 460

DRY 1200 WAVE

5 880

micro COMPRESSOR +

ultra QUIET +

easy INSTALL +



1. Installation:

S standard: on the floor	0
M on the wall (floor feet + wall console)	135

2. Control:

S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)	0
E remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)	345
W6 remote wired humidistat EBERLE HYG6001 + built-in touch controller	120
W7 remote wired humidistat & thermostat EBERLE HYG7001 + built-in touch controller	140

3. Air temperature:

S standard: +9°C...+36°C	0
B +9°C...+42°C (high temperature set)	270

4. Air heating:

S standard: without LPHW (Low Pressure Hot Water)	0
H LPHW, 7 kW, without regulation	345
V LPHW, 7 kW, with solenoid valve, fully automated regulation	590
E Electrical heating 2.5 kW	570

5. LPHW connection:

S standard: N/A (without LPHW)	0
B from the back	0
R from right	0

6. micro LIGHT +




S standard: without Pool Security microLIGHT+	0
L Pool Security microLIGHT+	140

7. Air filter:

S standard: without air filter	0
F Air filter (for model with wall or mobile stand installation: 1-S/M option)	54

8. Fresh air supply:

S standard: without fresh air supply	0
F adapter, Ø 100 mm, 50 mm length, galvanized	35



EURO PALETTE packed, FUMIGATED

17.50€/1pc

(Depending on the model it is possible to pack more units on EUP (2-6pcs).)

90l
90 m²

DRY 800 METAL / ORIENT

120l
120 m²

DRY 1200 METAL / ORIENT

NEW
DESIGN

Cover	Extraction rate (30°C/60% RH - 35°C/95% RH)	Air flow	Extraction rate (30°C/60% RH - 35°C/95% RH)	Air flow
metal	90-180 l/24hrs	1100 m ³ /hour	120-240 l/24hrs	1200 m ³ /hour

DRY 800M - 1. - 2. - 3. - 4. - 5. - 6. - 7. - 8. - 9. 
DRY 1200M - 1. - 2. - 3. - 4. - 5. - 6. - 7. - 8. - 9.
 Wi-Fi included



SWIMMING POOL DEHUMIDIFIERS

Basic equipment:	Model:	Price EXW w/o VAT /EUR/
Dehumidifier, floor feet, user's manual	DRY 800 METAL / ORIENT	5 980
   	DRY 1200 METAL / ORIENT	6 500

1. Color options:

W standard: white (RAL9010)	0
S silver color ,Silver grey' - Tiger	130
C color selection according to your preference (RAL code) - 200+ colors	price on demand

2. Installation:

S standard: on the floor	0
M on the wall (floor feet + wall console)	135
P through-the-wall INDOOR INSTALLATION (main chassis cover from galvanized metal powder coated RAL9010 with AIR IN from the back, AIR OUT to the back/to the top, including the through-the-wall ducts set and removable grills, insulated from the inside)	325
E through-the-wall OUTDOOR INSTALLATION (40mm TTW external aluminum and rubber insulation, winter module, condensate tray defrost, -15°C)	895

3. Control:

S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)	0
E remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)	345
W6 remote wired humidistat EBERLE HYG6001+built-in touch controller	120
W7 remote wired humidistat & thermostat EBERLE HYG7001+built-in touch controller	140

4. Air temperature:

S standard: +9°C...+36°C	0
B +9°C...+42°C (high temperature set)	270

5. Air heating:

S standard: without LPHW (Low Pressure Hot Water)	0
H LPHW, 7 kW, without regulation	345
V LPHW, 7 kW, with solenoid valve, fully automated regulation	590
E Electrical heating 2.5 kW	570

6. LPHW connection:

S standard: N/A (without LPHW)	0
B from the back	0
R from right	0

7.



S standard: without Pool Security microLIGHT+	0
L Pool Security microLIGHT+	140

8. Air filter:


S standard: without air filter	0
F Air filter (for model with wall or floor installation: 2-S/M option)	54
C Air filter grid (for model with TTW installation: 2-P/E option) (G3 class)	67

9. Fresh air supply:

S standard: without fresh air supply	0
F adapter, Ø 100 mm, 50 mm length, galvanized	35



EURO PALETTE packed, FUIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)



DRY Salt+ Sulphur+

Applicable
to all models
of dehumidi-
fiers

8x
more
reliable
use

3%
wt/wt
Maximum salt
content

30
kg/m³
Maximum salt
content

Models:	Price EXW /* w/o VAT /EUR/ 1-5 pcs	Price EXW /* w/o VAT /EUR/ 6-14 pcs	Price EXW /* w/o VAT /EUR/ 15 pcs+
DRY 300 Salt+ Sulphur+	1 380	1180	880
DRY 400 Salt+ Sulphur+	1 380	1180	880
DRY 500 Salt+ Sulphur+	1 560	1 360	1 060
DRY 800 Salt+ Sulphur+	1 740	1 540	1 240
DRY 1200 Salt+	1 740	1 540	1 240

/* **Brutto Price List price.**
Distributor rebates apply.

Basic description:

Special treatment to withstand high concentrations of salt, sulphur and chlorine. Designed for natural salt/sulphur water spa, salt caves or alternatives with natural water spring spa that contains high concentrations of salt or sulphur. This special treatment can be applied also to high chlorine concentration pools where it provides higher resistance thereby longer livelihood of the device. Treatment is also designed to avoid formation of sulphuric acid (H₂SO₄).

- Natural spa
- Salt caves
- Chlorine
- Sulphur

- Extra zinc
- Extra LCE Epoxy coating
- Extra powder coating enamel at 180°
- Extra brex insulation



Special treatment to withstand high concentration
of **SALT, SULPHUR and CHLORINE.**

Suitable for natural salt/sulfur
water spa, salt caves and
pools with high concentration
of salt, sulfur or chlorine.



DRY Salt+ Sulphur+

**PROLONGS
LIVELIHOOD OF
YOUR DEHUMIDIFIER**

IN EXTREME CONDITIONS



Applicable to
all models of
pool dehu-
midifiers

**8x
more
reliable use**

 **MICROWELL**

LEADING EUROPEAN SWIMMING POOL DEHUMIDIFIERS MANUFACTURER

www.microwell.eu

32 l
30 m²

DRY 300 DUCT

Cover	Extraction rate (30°C/60% RH - 35°C/95% RH)	Air flow
metal	32-63 l/24hrs	500 m ³ /hour, 200 Pa



DRY 300D - 1. - 2. - 3. - 4. - 5. - 6. - 7.

Basic equipment:

Dehumidifier, wall console, fixation screws, user's manual, installation layout

Price EXW
w/o VAT /EUR/

3 770

micro COMPRESSOR+

micro CONTROL+



1. Installation:

S standard - INDOOR: on the wall	0
E through-the-wall OUTDOOR INSTALLATION (40mm TTW external aluminum and rubber insulation, winter module, condensate tray defrost, -15°C)	535

2. Control:

S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)	0
E remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)	345
W6 remote wired humidistat EBERLE HYG6001+built-in touch controller	120
W7 remote wired humidistat & thermostat EBERLE HYG7001+built-in touch controller	140

3. Air temperature:

S standard: +9°C...+36°C	0
V +9°C...+42°C (high temperature set)	259
F +5°C...+35°C (low temperature set with 4-way valve hot gas defrost)	385

4. Air heating:

S standard: without LPHW (Low Pressure Hot Water)	0
H LPHW, 3.5 kW, without regulation	228
V LPHW, 3.5 kW, with solenoid valve, fully automated regulation	442
E Electrical heating, 2 kW	490

5. LPHW connection:


S standard: N/A (without LPHW)	0
B from the back	0
R from right	0

6. Air filter console:

S standard: without air filter console	0
C Air filter console 5C, with removable cartouche (G3 - class)	150


7. Air ducting connection:

S1 Air inlet from bottom	0
S2 Air outlet from the top	0
F1 Air inlet from the front	80
F2 Air outlet from the front	80



EURO PALETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)

Find more **ACCESSORIES**
on pages 61-75.



43 l
40 m²

DRY 400 DUCT

Cover	Extraction rate (30°C/60% RH - 35°C/95% RH)	Air flow
metal	43-78 l/24hrs	500 m ³ /hour, 200 Pa




DRY 400D - 1. - 2. - 3. - 4. - 5. - 6. - 7.

Basic equipment: Price EXW w/o VAT /EUR/

Dehumidifier, wall console, fixation screws, user's manual, installation layout

micro COMPRESSOR+
micro CONTROL+
FREE 3 YEARS WARRANTY
Wi-Fi included
4 180

1. Installation:	
S standard - INDOOR: on the wall	0
E through-the-wall OUTDOOR INSTALLATION (40mm TTW external aluminum and rubber insulation, winter module, condensate tray defrost, -15°C)	535
2. Control:	
S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)	0
E remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)	345
W6 remote wired humidistat EBERLE HYG6001+built-in touch controller	120
W7 remote wired humidistat & thermostat EBERLE HYG7001+built-in touch controller	140
3. Air temperature:	
S standard: +9°C...+42°C	0
4. Air heating:	
S standard: without LPHW (Low Pressure Hot Water)	0
H LPHW, 3.5 kW, without regulation	228
V LPHW, 3.5 kW, with solenoid valve, fully automated regulation	442
E Electrical heating, 2 kW	490
5. LPHW connection:	
S standard: N/A (without LPHW)	0
B from the back	0
R from right	0
6. Air filter console:	
S standard: without air filter console	0
C Air filter console 5C, with removable cartouche (G3 - class)	150
7. Air ducting connection:	
S1 Air inlet from bottom	0
S2 Air outlet from the top	0
F1 Air inlet from the front	80
F2 Air outlet from the front	80




EURO PALETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)

52 l
50 m²

DRY 500 DUCT

Cover	Extraction rate (30°C/60% RH - 35°C/95% RH)	Air flow
metal	52-132 l/24hrs	1000 m ³ /hour, 200 Pa



DRY 500D - 1. - 2. - 3. - 4. - 5. - 6. - 7.

Basic equipment: Price EXW w/o VAT /EUR/

Dehumidifier, wall console, fixation screws, user's manual, installation layout

micro COMPRESSOR+

micro CONTROL+



4 900

1. Installation:

S standard - INDOOR: on the wall	0
E through-the-wall OUTDOOR INSTALLATION (40mm TTW external aluminum and rubber insulation, winter module, condensate tray defrost, -15°C)	586

2. Control:

S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)	0
E remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)	345
W6 remote wired humidistat EBERLE HYG6001+built-in touch controller	120
W7 remote wired humidistat & thermostat EBERLE HYG7001+built-in touch controller	140

3. Air temperature:

S standard: +9°C...+36°C	0
V +9°C...+42°C (high temperature set)	259
F +5°C...+35°C (low temperature set with 4-way valve hot gas defrost)	385

4. Air heating:

S standard: without LPHW (Low Pressure Hot Water)	0
H LPHW, 5 kW, without regulation	228
V LPHW, 5 kW, with solenoid valve, fully automated regulation	442
E Electrical heating, 2 kW	490

5. LPHW connection:


S standard: N/A (without LPHW)	0
B from the back	0
R from right	0

6. Air filter console:


S standard: without air filter console	0
C Air filter console 5C, with removable cartouche (G3 - class)	170

7. Air ducting connection:


S1 Air inlet from bottom	0
S2 Air outlet from the top	0
F1 Air inlet from the front	80
F2 Air outlet from the front	80



EURO PALETTE packed, FUMIGATED
17.50€/1pc
(Depending on the model it is possible to pack more units on EUP (2-6pcs).)




Find more ACCESSORIES on pages 61-75.



88l 80 m ²	DRY 800 DUCT			112l 110 m ²	DRY 1200 DUCT		
Cover	Extraction rate (30°C/60% RH - 35°C/95% RH)	Air flow		Extraction rate (30°C/60% RH - 35°C/95% RH)	Air flow		
metal	88-180 l/24hrs	1100 m ³ /hour, 170 Pa		112-240 l/24hrs	1200 m ³ /hour, 145 Pa		





DRY 800D - [1.] - [2.] - [3.] - [4.] - [5.] - [6.] - [7.]

DRY 1200D - [1.] - [2.] - [3.] - [4.] - [5.] - [6.] - [7.] Wi-Fi included



Basic equipment:	Model:	Price EXW w/o VAT /EUR/
Dehumidifier, floor feet, fixation screws, user's manual, installation layout 	DRY 800 DUCT	6 600
	DRY 1200 DUCT	7 080

1. Installation:		
S standard: INDOOR on the floor		0
M on the wall (floor feet + wall console)		235
E through-the-wall OUTDOOR INSTALLATION (40mm TTW external aluminum and rubber insulation, winter module, condensate tray defrost, -15°C)		660
2. Control:		
S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)		0
E remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)		345
W6 remote wired humidistat EBERLE HYG6001+built-in touch controller		120
W7 remote wired humidistat & thermostat EBERLE HYG7001+built-in touch controller		140
3. Air temperature		
S standard: +9°C...+36°C		0
B +9°C...+42°C (high temperature set)		285
4. Air heating:		
S standard: without LPHW (Low Pressure Hot Water)		0
H LPHW, 7 kW, without regulation		345
V LPHW, 7 kW, with solenoid valve, fully automated regulation		590
E Electrical heating 2.5 kW		570
5. LPHW connection:		
S standard: N/A (without LPHW)		0
B from the back		0
R from right		0
6. Air filter console:		
S standard: without air filter console		0
C Air filter console 5C, with removable cartouche (G3 - class)		250
7. Air ducting connection:		
A1 Air inlet from the back		0
A2 Air outlet from the back		0
B1 Air inlet from the front		80
B2 Air outlet from the front		80
C1 Air inlet from the bottom		80
C2 Air outlet from the top		0



EURO PALETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)

67 l 60 m²			134 l 120 m²	
SIREN Eco mono			SIREN Eco due	
Cover	Extraction rate <small>(30°C/60% RH - 35°C/95% RH)</small>	Air flow	Extraction rate <small>(30°C/60% RH - 35°C/95% RH)</small>	Air flow
plastic (acryl) white color	67-130 l/24hrs	1000 m ³ / hour	134-260 l/24hrs	2000 m ³ /hour

SIREN Eco mono - 1. - 2. - 3. - 4. - 5.



SIREN Eco due - 1. - 2. - 3. - 4. - 5.

Basic equipment:	Model:	Price EXW w/o VAT /EUR/
ceiling unit, compressor unit, remote control, wall consoles for compressor unit, ceiling lifting mechanism, Bluetooth speaker, LED light, user's manual	SIREN Eco mono	8 450
2x ceiling unit, compressor unit, remote control, wall consoles for compressor unit, ceiling lifting mechanism, Bluetooth speaker, LED light, user's manual	SIREN Eco due	13 900




- micro LIGHT +
- micro ENERGY +
- micro SAFETY +
- FREE 3 YEARS WARRANTY
- R32
- micro COMPRESSOR +
- ultra QUIET +

1. Ceiling unit installation:	
S concrete ceiling	0
B wooden beam	0
2. Cable length:	
S 10m	0
M 20m	70
L 30m	90
3. Copper pipes:	
S standard: without copper pipes	0
A Insulated copper pipes D10 (3/8" x 1)+D12 (1/2" x 1) - 50m package /Rebate not applicable. This is the final purchase price./	510
4. Condensate pump:	
S standard: built-in condensate pump, vertical discharge 1~8m, horizontal discharge 21~0m	0
E external condensate pump, vertical suction up to 3m, horizontal suction up to 10m, vertical discharge 1~8m, horizontal discharge 21~0m	40
A additional condensate pump Sauermann – condensing, with tank 2l, 500l/h, max. 5m	75
5. Condensate hose:	
S standard: with 1m condensate hose 6mm internal / 9mm external flexible	0
A Condensate hose #106008 6mm internal / 9mm external flexible	0.95



EURO PALETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)



Perfect dehumidification without limits

MICROWELL SIREN ECO is the ultimate superstar, the first ceiling swimming pool dehumidifier in the world. Combining all what Microwell technology has to offer, SIREN ECO is an intelligent and visually captivating solution of paramount performance, setting a new tide in the industry.

As the first round ceiling dehumidifier it is constructed as dual split unit, capable of all round and thorough humidity extraction.

**SPLIT
system**

**Wireless
control**

DEHUMIDIFIER



microLIGHT+



LOUDSPEAKER



LED LAMP



Siren Eco

up to 120 m² pool surface

94l 90 m ²	DRY 800 HORIZON	127l 120 m ²	DRY 1200 HORIZON
Cover	Extraction rate (30°C/60% RH - 30°C/80% RH)	Air flow	Extraction rate (30°C/60% RH - 30°C/80% RH)
metal - RAL 9010 white	94-141 l/24hrs	1150 m ³ /hour	127-194 l/24hrs 1800 m ³ /hour


DRY 800 HORIZON - 1. - 2. - 3. - 4. - 5. - 6. - 7.

DRY 1200 HORIZON - 1. - 2. - 3. - 4. - 5. - 6. - 7.




Basic equipment:	Model:	Price EXW w/o VAT /EUR/
Dehumidifier, user's manual	DRY 800 HORIZON	6 950
	DRY 1200 HORIZON	7 450

1. Installation:		
S ceiling-mounted (on threaded rods M8)		0
F floor-mounted (floor console)		120
W wall-mounted console		150




2. Exhaust direction (pool supply):		
H horizontal 600x200mm		0
D downward 600x200mm		0
U upward 600x200mm		0



Note: Suction (pool exhaust) is always horizontal 800x400mm.

3. Control:		
S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)		0
E remote wireless humidistat & thermostat DRY EASY 300 + built-in touch controller with WiFi and RS-485 (Modbus)		345
W6 remote wired humidistat EBERLE HYG6001+built-in touch controller		120
W7 remote wired humidistat & thermostat EBERLE HYG7001+built-in touch controller		140
R External touch controller (WIFI, RS-485 Modbus), 10m cable		90



4. Air temperature:		
S standard: +9°C...+36°C		0
B +9°C...+42°C (high temperature set)		270

5. External supplementary air heating (on exhaust)*:		
S without		0

HC1 hot water heater ILU 315 max output **14.5 kW** (90/70°C, 0.18 l/s, 5.9 kPa), on exhaust circular pipe dia 315 mm / length 200 mm, width 420 mm, height 355 mm, water connection diameter d 1/2" + solenoid 2-way valve d 1/2", **fully automatic regulation** 846

HC2 hot water heater ILU 400 max output **24.5 kW** (90/70°C, 0.3 l/s, 12.3 kPa), on exhaust circular pipe dia 400 mm / length 200 mm, width 495 mm, height 430 mm, water connection diameter d 1/2" + solenoid 2-way valve d 1/2", **fully automatic regulation** 956

EC electrical heater dia 315-400mm max output **9.0 kW** upon request


*Note: It is necessary to insert approximately 1m of air ducting between the fan and the heater to avoid fan motor overheating.



6. External filter cartridge (on suction):		
S standard: without air filter		0
C external filter cartridge with flat filter on the intake rectangular pipe 800 x 400 mm / length 200-250 mm (G3 class)		280




7. Air ducting adapters:		
S Without adapters		0
R1 rounded adapters for dia 315 mm / length 400 mm on suction and exhaust (2 pcs), axis		170
R2 rounded adapters for dia 400 mm / length 400 mm on suction and exhaust (2 pcs), axis		180
O other - rectangular, square, double, axis/non-axis		upon request





HORIZON DRY

New concept of concealed and ducted swimming pool dehumidifiers



3 air directions
for connection available



MICROWELL

LEADING EUROPEAN SWIMMING POOL DEHUMIDIFIERS MANUFACTURER

www.microwell.eu

22 l
90 m³/*

DRY 300 GALLERY

38 l
135 m³/*

DRY 400 GALLERY

Cover	Extraction rate (25°C, 50%RH)	Air flow	Extraction rate (25°C, 50%RH)	Air flow
wooden wardrobe construction	22 l/24hrs	550 m ³ /h	38 l/hrs	600 m ³ /h




DRY 300G - **1.** - **2.** - **3.**


DRY 400G - **1.** - **2.** - **3.**

Basic equipment:	Model:	Price EXW w/o VAT /EUR/
Fully mobile dehumidifier, 20 liter condensation tank, mobile cart, water tank drainage, float switch, user's manual micro COMPRESSOR+	DRY 300 GALLERY	3 390
	DRY 400 GALLERY	3 590

1. Control:		
S standard: built-in digital touch controller with WiFi and RS-485 (Modbus)		0
2. Air temperature:		
S standard: +9°C...+36°C		0
F +5°C...+36°C (with 4-way valve hot gas defrost) low temperature set		246
3. Air filter:		
S standard: without air filter		0
F Air filter		56



Basic equipment includes:



 EURO PALLETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)

Warranty period: 5 years compressor + titanium exchanger | 2 years other components



Suitable for small exhibition spaces

Picture is illustratory.

40 l day	T40 TE40		90 l day	T90 TE9		120 l day	T120 TE120	
Cover	Operating range	Nominal air delivery	Operating range	Nominal air delivery	Operating range	Nominal air delivery		
metal	0°C - 35°C	500 m³/hour	0°C - 35°C	1100 m³/hour	0°C - 35°C	1500 m³/hour		



ENERGY CONSUMPTION
from **650W**




/* Final prices. Discount does not apply on these items.


Basic equipment:	Price EXW /* w/o VAT /EUR/
Fully mobile dehumidifier, user's manual, EU plug, on-off	
Designed for drying up buildings, new construction sites, warehouses, as well as non-heated and flooded buildings with high level of humidity.	
easy INSTALL+	
T40	1 300
TE40	1 400
with Electrical heater, 2 kW	
T90	1 800
TE90	1 990
with Electrical heater, 2 kW	
T120	2 100
TE120	2 250
with Electrical heater, 2 kW	

Additional equipment:	Price EXW /* w/o VAT /EUR/
A UK plug conversion	20
B Float switch	90
C External hygostat	100
D 20l bucket with mobile base (4 wheels)	85



T40 | TE40



T90 | TE90



T120 | TE120



Picture is illustratory.

Suitable for construction sites, buildings, rooms after reconstruction

EURO PALETTE packed, FUMIGATED
17.50€/1pc (Depending on the model it is possible to pack more units on EUP (2-6pcs).)



ACCESSORIES & Spare parts

Measurement and regulation
Installation material and equipment
Spare parts
Water surface covering
Ventilation

**The widest selection of finishes
and accessories.**

Benefits that customers desire

Based on close relationship with customers, Microwell provides functionality through matchless selection of accessory options.

Qmax - Heat pump TESTER

Save up to
30%
on energy
bill



FOR SETTING THE QUALITY
of pool performance

www.microwell.eu

ACCESSORIES & Spare parts

Carry-on measurement device designed to provide measurement and optimization of heat pump's performance and efficiency

Price EXW
w/o VAT /EUR/

Basic equipment:

- Carry on measurement device with inductive flow meter KROHNE Optiflux 2050 with connection DN50
- A pair of mobile WIKA Pt100 resistance thermometers
- Measurement device



1. Qmax-TESTER


measures: water temperature inlet & outlet, true heating or cooling output, heat pump power consumption, water flow
counts: Coefficient of performance /COP/, Energy efficiency ratio /EER/

2 890

2. Heat pump's OPTIMIZATION

executed by a Microwell trained technician

99



IMMEDIATE TESTING
OF A HEAT PUMP



COMPATIBLE
WITH ALL 1 PHASE HP

WATCH VIDEO & LEARN MORE



/General discount does not apply on above stated prices.
Stated prices are final./

v. 01/2024

MICROWELL

1. FLOAT SWITCHES FOR EQUALIZING TANKS

Float switches for equalizing tanks	Price EXW w/o VAT /EUR/
-------------------------------------	----------------------------

1.1. NIVOCONT - conductive level switch

1.1.A KSN-201 - probe from stainless steel	33.60
--	-------


1.1.B KRK-512-5 - relay	47.30
-------------------------	-------

1.2. NIVOFLOAT - plastic level switch

1.2.A NLP-110 - plastic level float switch (PVC cable 10m)	31.80
--	-------

1.3. NIVOPOINT - multiple switching point magnetic level switch:

1.3.A MRA-210-3 - multiple switching point level switch with wetted parts from stainless steel (1" thread, 2 switching points, probe tube 1m)	204.00
---	--------




2. HUMIDITY AND TEMPERATURE METER in 1

Device for indoor humidity and temperature measuring	Price EXW w/o VAT /EUR/
--	----------------------------

2.1. Thermo-humidistat BEURER HM 16

Humidity 20% to 95% Air temperature 0°C ~ +50°C Selection °C/°F Wall installation / flipping holder Well readable display Measurement accuracy ± 5% Battery 1x 1.5V	14.40
---	-------




2.2. PROFESSIONAL- GFTH 95 (professional application)

Humidity measurement accuracy: ± 1,5% 1 line LCD Battery included 1x 9V, typ IEC 6F22 Body: ABS	153.00
--	--------



/Change in price and offered products reserved./

3. HUMIDITY VISUALIZATION



microLIGHT+

Price EXW
w/o VAT /EUR/

3.1. microLIGHT+ INFINITY

Operational temperature range: 0°C ... +60°C.
Compatibility: All DRY range

3.1.A microLIGHT+ INFINITY, length 1 m	183.00
3.1.B microLIGHT+ INFINITY, length 3 m	213.00
3.1.C microLIGHT+ INFINITY, length 5 m	228.00

3.2. microLIGHT+ LAMP

A freestanding table lamp.
MicroLIGHT+ LAMP measures and automatically reflects current relative humidity, changing the colour gradient between blue, green and red colour.


3.2.A microLIGHT+ LAMP	105.00
------------------------	--------

/Change in Lamp model reserved./

3.3. microSTEAM+

Operational temperature range: 0°C ... +120°C.
Designed for ceilings of the swimming pool halls as LED humidistat for saunas.

3.3.A microSTEAM+, length 1 m	229.00
3.3.B microSTEAM+, length 2 m	253.00



ACCESSORIES & Spare parts


Low humidity 0-40% RH

Ideal humidity 40-60% RH

High humidity 60-100% RH

microLIGHT+

Integrated LED light strip indicating current humidity in a pool. Light spectrum from blue (humidity low) through green (all OK) to red (problem – humidity high) in full color gradient.



v. 01/2025

MICROWELL


4. FLOOR GRILLS

Price change reserved

/Actual price to be quoted based on an individual enquiry./ **Price EXW**
w/o VAT /EUR/


4.1. Basic structure

4.1.A Symmetrical ASS	from 154.00
4.1.B Asymmetrical ASU	from 160.00
4.1.C Asymmetrical removable ASR	from 207.00
4.1.D LED Asymmetrical removable ASR	from 352.00




4.2. Fixation

4.2.A Mounting rail AS-BF	from 34.50
4.2.B Substructure channel AS-UBK	from 252.00



4.3. Accessories

4.3.A Comer AS-GS	from 69.90
4.3.B Diffuser AS-DLV	from 11.40
4.3.C Construction works protection cover AS-AP	from 6.50
4.3.D Cut out for substructure channel AS-UBK-A	from 13.00
4.3.E Substructure channel socket AS-UBK-ZSR	from 28.40
4.3.F Side cut out with socket for mounting rail or substructure channel AS-UBK-ZS	from 28.40
4.3.G End cover AS-END	from 16.80
4.3.H Condensate drain for substructure channel AS-UBK-AS	from 47.00



/Price change reserved./



5. INSTALLATION MATERIAL

5.1 for SWIMMING POOL DEHUMIDIFIERS installation		unit	Price EXW w/o VAT /EUR/
Pumps and accessories			
7102	Pump SI 83 – condensing, with tank 2l, 500l/h, max. 4.2m /No. 7012/	1 pc	79.00
7100	Condensate hose 16mm internal / 20mm external flexible /No. 7100/	1 standard meter	0.95
Cleaning and disinfection appliances			
5008	Easy Care spray – evaporator cleaner and disinfection /No. 5008/	1 pc	14.10
In-wall condensate siphons			
7103	In-wall condensate siphon, DN32/20 /No. 7103/	1 pc	32.00
Anti odor siphons			
7102	Siphon (anti-odor trap) for condensation hose /No. 7102/	1 pc	7.00
5.2 for SWIMMING POOL HEAT PUMP installation		unit	Price EXW w/o VAT /EUR/
Copper pipes			
2011	for HP900/1100 BLACK SPLIT, HP1100 SILVER INVERTER Pro SPLIT Insulated double copper pipes DUO 6+12 (1/4"+1/2" x 0.8) - 25m package /No. 2011/	1m	6.50
2012	for HP1500/1700/2100 SILVER Inverter Pro SPLIT, HP 1500 BLACK Insulated double copper pipes DUO 10+16 (3/8" x 5/8") - 25m package /No. 2012/	1m	10.00
2003 2007	for HP2300/2800 INVENTOR, HP2400/3000 PREMIUM, HP2700 SILVER INVERTER Pro SPLIT Insulated copper pipes d10 (3/8" x 1.0)- 50m package /No. 2003/ + insulated copper pipes d18 (3/4" x 1.0)- 25m package /No. 2007/	1m	13.00
2005 2003	for DRY SIREN Insulated copper pipes d12 (1/2" x 1.0)- 50m package /No. 2005/ + insulated copper pipes d10 (3/8" x 1.0)- 50m package /No. 2003/	1m	10.50
Insulation tape			
5.2.2.A	A self-adhesive insulation tape K-flex white /No. 2016/	1 pc	13.40
Consoles and base blocks			
6004	Console White - 700, 2 pcs	set	44.00
6061	Base installation block 450 – white, carrying capacity 200kg, 2pcs /No. 6055/, with Side covers, 4 pcs	set	8.60
6065	Rubber base installation block 400mm - black, carrying capacity 200kg. Set includes 2pcs. Price is stated for 1pc Compatibility: HP 900 - 1100 BLACK	set	26.40
6066	Rubber base installation block 600mm - black, carrying capacity 200kg. Set includes 2pcs. Price is stated for 1set. Compatibility: HP 1100-1500-1800-2100-2800 SILVER INVERTER Pro, HP2300-3000, INVENTOR & PREMIUM, HP 1500 BLACK	set	34.80
6023	Antivibration silentblocks, 4pcs	set	16.80



/Price change reserved./

General discount does not apply on above stated prices. Stated prices are final.



6. EQUIPMENT FOR INSTALLATION AND SERVICE

Price change reserved



Price EXW
w/o VAT /EUR/

6.1. Vacuum pump

6.1.A Vacuum pump Rothenberger ROAIRVAC 6,0 - 170l/min **325**

6.1.A



6.1.B Refco - ENVIRO DUO OS, recovery station with oil separation - 4687035, gas 33kg/h, liquid 210 kg/h, Push pull 570kg/h **1 140**

6.1.B



6.2. Charging and testing hoses Refco

6.2.A Premium with closure valve, length 90cm **50**

6.2.B Premium with closure valve, length 150cm **60**

6.2.A|B



6.3. Manifold valve Refco

6.3.A for refrigerant R410, R32 **95**

6.3.A



6.3.B for refrigerant R22, R407, R410 **85**

6.3.B

6.4. Eccentric flare tool

6.4.A Eccentric flare tool Rothenberger, with 1" flare matrix, 222402 **150**

6.4.A



6.4.B Eccentric flare tool REFCO, with 1" flare matrix in small suitcase, RF888Z **120**

6.4.B



6.4.C Eccentric flare tool REFCO, flare matrix and cutter in small suitcase, RF275FS **90**

6.4.C



6.4.D Flare tool Rothenberger with expanding - 1" packet **55**

6.4.D



6.5. Expanders

6.5.A Expander Rothenberger 3/8, 1/2, 5/8, 3/4, 22, 28 - 1" packet, 12320 **340**

6.5.A



6.6. Cutters

6.6.A Cutter Rothenberger MINIMAX 3 - 28mm, 70015 **25**

6.6.A



6.6.B Cutter Rothenberger TC 35, 6- 35mm, 70027 **30**

6.6.B



6.7. Tube benders

6.7.A Tube bender Rothenberger TBM 3/8, 1/2, 5/8, 3/4, 7/8, 23022X **225**

6.7.A



6.8. Charging scales

6.8.A Charging scale Rothenberger to 120kg - accuracy 2g, 173004 **275**

6.8.A



6.8.B Charging scales TST **170**

6.8.B



/Price and model change reserved./

7. WATER CONNECTION PACKET

Price change reserved



for HEAT PUMP CONNECTION to pool water circuit

	/Price for the whole set/	Price EXW w/o VAT /EUR/
7. 1.	WATER CONNECTION PACKET for HP Premium, Inventor	155.00
7. 2.	WATER CONNECTION PACKET for HP SILVER Inverter Pro	135.00



1 Pressure hose d50, length 10m /No. 211055/

2 PVC tube d50, length 0.8m /No. 211061/

3 Tube holder, open, d50, 8pcs /No. 211050/

4 Hose nut / Swivel for glue d50 x external thread 1 1/2", 2pcs /No. 211049/

5 PVC tube knee 90° for glue, 8pcs /No. 211046/

6 Swivel with valve for glue d50, 3pcs /No. 211048/

7 PVC "T" piece 90° for glue d50, 2pcs /No. 211047/

8 Glue Tangit PVC-U, 250g /No. 211051/

9 Cleaner Tangit 125 ml /No. 211052/

10 Sealing fibre Tangit Uni-Lock, 1 package /No. 211054/

11 Teflon tape 12 mm/12 m /No. 211053/

12 Screw fasteners with screws, 8pcs, dimensions: 10x48mm /No. 206013/

13 Screw fasteners with screws, 8pcs, dimensions: 6x70mm /No. 206023/

14 Cardboard box, 800x600x600 mm /No. 210005/

/Price change reserved./

General discount does not apply on above stated prices.
Stated prices are final.



SMART PURCHASE
Buy the whole set.



/Picture is illustratory./

ACCESSORIES & Spare parts



v. 01/2025



8. SPARE PARTS

8.A.

DEHUMIDIFIER SPARE PARTS

Price EXW
w/o VAT /EUR/

Order code	Compressors	Price
103322	Compressor DRY 300: including siphon, silentblocks, heat protection, cover, Daikin OEM	305
112003	Compressor DRY 300: including siphon, silentblocks, heat protection, cover, LG	485
103008	Compressor DRY 500: including siphon, silentblocks, heat protection, cover, Daikin OEM	415
112004	Compressor DRY 500: including siphon, silentblocks, heat protection, cover, LG	575
103015	Compressor DRY 800: including siphon, silentblocks, heat protection, cover	840
103016	Compressor DRY 1200: including siphon, silentblocks, heat protection, cover	1 065
103005	Compressor capacitor DRY500: 30mF	10
103050	Compressor capacitor DRY300/400: 40mF	10
103018	Compressor capacitor DRY800/1200:	12



Order code	Compressor	Price
103022	Humidistat & Thermostat DIGITAL (FOX-2SHTR) BUILT-IN SILVER, METAL a DUCT	126
103020	Mechanical built-in humidistat /rotary/ ALL DEHUMIDIFIER MODELS	29
103021	Indication wheel for rotary humidistat / ALL DEHUMIDIFIER MODELS	2
103026	Mechanical external rotary humidistat EBERLE HYG-6001	80
103028	Mechanical external rotary humidistat EBERLE HYG-7001	85
RHT-RX	Receiver for wireless humidistat & thermostat DRY EASY 300	70
RHT-TX-2	Transmitter for wireless humidistat & thermostat DRY EASY 300	215
RHT-ANT	Antenna for wireless humidistat & thermostat DRY EASY 300	60
103464	Main board of dehumidifier controller DRY (SW:SRO193040-1) PCB	180
103465	Round touch controller DRY (SW: SRO193039) wih WiFi	85



Order code	Sensors for	Color	Price
103471	T1 SH humidity sensor 80cm CHTM-02NA-800-XH	White	15.00
103468	T2 Compressor discharge 50kohm copper head sensor 120cm CC.T37	Red	CC.T452 4.50
103466	T3 Suction/Condenser 5kohm copper head sensor 120cm CC.T43	Black	CC.T118 3.50
103474	T4 Evaporator 5kohm copper head sensor 120cm CC.T43	Yellow	CC.T189 3.00
103469	T5 Air temperature 5kohm plastic head sensor 80cm CC.T45	White	CC.T45 3.00



Order code	Sensors for DRY800-1200	Color	Price
103472	T1 SH humidity sensor 1500cm CHTM-02NA-1500-XH	White	15.00
103468	T2 Compressor discharge 50kohm copper head sensor 120cm CC.T37	Red	CC.T452 4.50
103467	T3 Suction/Condenser 5kohm copper head sensor 200cm CC.T63	Black	CC.T336 3.50
103475	T4 Evaporator 5kohm copper head sensor 200cm CC.T63T2 Compressor discharge	Yellow	CC.T337 3.50
103470	T5 Air temperature 5kohm plastic head sensor 150cm CC.T112T2 Compressor discharge	White	CC.T112 3.00



8. SPARE PARTS

8.A.

DEHUMIDIFIER SPARE PARTS

Price EXW
w/o VAT /EUR/


Order code	Valves	Price
103004	LP valve - DRY 300/400	19
103010	LP valve - DRY 500/800/1200	19
103059	Time relay JEL-111 - ALL DEHUMIDIFIER MODELS	35
103058	Power relay Finder - DRY 300/400/500/800/1200 30A	19
103069	Power relay OMRON DRY 800/1200	25
108001	Filling valve d6/100mm, SAE 1/4" ALL DEHUMIDIFIER MODELS	3
103019	Antifreeze thermostat +15°C	35

Order code	Capilla	Price
108006	Capillary DRY300, length: 1m	5.50
108016	Capillary TLEX 2.0, DRY400	5.50
108006	Capillary DRY500, length: 2.6 m	10.50

Order code	Refrigerant filters and air filters	Price
108032	Refrigerant filter Castel 300/400/500	11.00
108022	Refrigerant Filter DRY800/1200	14.00
F1	Air Filter DRY300/400 TTW, G3	5.00
F2	Air Filter DRY500 TTW, G3	5.00
F3	Air Filter DRY800/1200 TTW, G3	5.00
F4	Air Filter DRY300/400 DUCT, G3	6.00
F5	Air Filter DRY500 DUCT, G3	7.00
F6	Air Filter DRY800/1200 DUCT, G3	9.00

Order code	Fans	Price
103442	Fan for DRY 300-400-500-800-1200. DRY300-400 - 1pc/dehumidifier, DRY500-800-1200	142
103009	Ventilator DUCT 300/500/800/1200 Ziehl-Abegg	240
103012	Fan capacitor DUCT DRY 500-800-1200: 3.5µF 400/450V	10

General discount does not apply on above stated prices.
Stated prices are final.



8. SPARE PARTS

8.B.

HEAT PUMP SPARE PARTS

Price EXW
w/o VAT /EUR/

Order code	Flow switch	Price
203005	Flow switch HP1000-1100-1400-1500-1700-2300-2400-2800-3000	35
Exchangers		
204003	Exchanger Inventor HP2300	425
204004	Exchanger Inventor HP2800	525
Controllers		
HP18010	Controller - complete set HP1000, 2000, 30000, SW-SRO193032, SRO193033	199
203022	Controller - Transformer	20
203008	Controller - Wall installation box	3
Wi-Fi box		
203051	WIFI box SRO193034, 2x 1m connection cable, female and male connector	30
Temperature sensors		
203011	Temperature sensor T1, T2, T5 (water, evaporator) (k5Ω)	3
203013	Temperature sensor T3 (air, plastic) (k5Ω)	3
203012	Temperature sensor T4 (compressor)(k50Ω)	3



8. SPARE PARTS

8.B.

HEAT PUMP SPARE PARTS

Price EXW
w/o VAT /EUR/


Order code	Fan blades	Price
209045	Fan blade HP 1000-1100-1400-1500	50
209035	Fan blade HP 2300-2400-2800-3000	50
209029	Fan Motor HP 2300-3000	150

Compressors		
209083	Compressor HP1000-1100, GMCC Rotary	550
209084	Compressor HP1400-1500, GMCC Rotary	660
209090	Compressor HP2300-2400, Panasonic Scroll	790
209089	Compressor HP2800-3000, Panasonic Scroll	890

Others		
209024	4-way valve electrical coil + copper valve HP1000-1100-1400-1500	30
209034	4-way valve electrical coil + copper valve HP2300-2400-2800-3000	30
HP18020	Set of silentblocks (4pcs)	18
HP18021	Condensate drain "L" part 90°	3
209029	Fan Motor C048 HP2300-2800-2400-3000	150
209031	Phase monitor HP2000-3000	60



General discount does not apply on above stated prices.
Stated prices are final.



8. SPARE PARTS

8.C.

HEAT PUMP SPARE PARTS for models HP SILVER

Price EXW
w/o VAT /EUR/

Round touch controller DRY (SW: SRO193039) with WiFi

Fan Blade	40
Fan Motor	110
Main Control Board	210
Reactor	20

HP1500 SILVERINVERTER PRO (220-240V~/50Hz)

Fan Blade	70
Fan Motor	120
Main Control Board	250
Reactor	20

HP1800 SILVERINVERTER PRO (220-240V~/50Hz)

Fan Blade	70
Fan Motor	120
Main Control Board	250
Reactor	20

HP2100 SILVERINVERTER PRO (220-240V~/50Hz)

Fan Blade	70
Fan Motor	120
Main Control Board	340
Reactor	20

HP2800 SILVERINVERTER PRO (380-415V/3N~/50Hz)

Fan Blade	40
Fan Motor	110
Main Control Board	120
Driver Board	540
Reactor	20

Universal Spare Parts for all the SIP Models

Water Flow Switch	35
Inlet/Outlet Water Connection (50mm)	10
Exhaust Temperature Sensor (compressor)	3.00
Temperature Sensor can be used for Coil Temperature, Suction Temperature, Cooling Coil Temperature, Inlet and Outlet Water Temperature	3.00
Ambient Temperature Sensor	4.00
Wire Controller Extended Cable (0.8m)	10
Wire Controller with Wi-Fi (Round Shape)	70



9. WATER SURFACE COVER

Price change reserved

A swimming pool cover reduces the actual evaporation by 30-50%. This means that you need a smaller dehumidifier for a given pool, you will save on energy bill since smaller unit consumes less electricity and also you will reduce heat losses of your water, thus you will need smaller heating device (heat pump) and also it will consume less energy compared to pool without cover.

Blue bubble plastic cover is a perfect solution for a domestic or hotel pool.



9.1 POOL COVER ROLLER

Price EXW

w/o VAT /EUR/

9.1.1. Pool cover roller - FIXED POSITION

9.1.1.A with telescopic tube length 2.7 - 4.4m **188**

9.1.1.B with telescopic tube length 3.7m - 5.4m **208**

9.1.1.C with telescopic tube length 4.1m - 5.7m **185**

9.1.1.D with telescopic tube length 5.3m - 6.9m **210**

9.1.2. Pool cover roller - MOBILE

9.1.2.A with telescopic tube length 2.7 - 4.4m **200**

9.1.2.B with telescopic tube length 3.7m - 5.4m **218**

9.1.3. Pool cover roller - SIDEWISE MOBILE

9.1.3.A with telescopic tube length 2.7 - 4.4m **250**

9.1.3.B with telescopic tube length 3.7 - 5.4m **275**

9.1.4. Pool cover roller - STANDING

9.1.4.A with telescopic tube length 2.7 - 4.4m **190**

9.1.4.B with telescopic tube length 3.7m - 5.4m **205**

9.1.5. Pool cover roller - FIXED ON THE WALL

9.1.5.A with telescopic tube length 2.6 - 4.3m **280**



9.2 BLUE BUBBLE PLASTIC SHEET

Price EXW

w/o VAT /EUR/


400 micr., 50m reel up, Light blue Geo Bubble material /m/

9.2.A width 3m **16.50**

9.2.B width 3.5m **19.50**

9.2.C width 4m **22.50**

9.2.D width 5m **27.50**



General discount does not apply on above stated prices. Stated prices are final.



10. VENTILATION

up to
300 m³/h

FREE
heated

Fan scheme



Price EXW
w/o VAT /EUR/

10.1. EXHAUST ventilation set

10.1.A Ventilation set A: Air flow: 100m³/h, Ø 100mm

Includes:

- Small axial extract fan DECOR 100
- Backdraft shutters RSK 100 ED
- Plastic external louvre LG100
- Plastic circular hose UK-PP 100/1000

120



10.1.B Ventilation set B: Air flow: 300m³/h, Ø 160mm

Includes:

- Small axial extract fan DECOR 300 SZ IPX4
- Backdraft shutters RSK 150 ED
- Plastic external louvre LG 150
- Plastic circular hose UK-PP 150/1000

150

Price EXW
w/o VAT /EUR/

10.2. FRESH AIR ventilation set

10.2.A FRESH AIR ventilation set A: with Fixed plastic external louvre

- Air flow: 100-300m³/h, Ø 100mm
- white color - RAL 9010
- Includes: Plastic circular hose LG100, Plastic circular hose UK-PP 100/1000

40



10.2.B FRESH AIR ventilation set B: with Electric plastic back draft louvre shutter


- Air flow: 100-300m³/h, Ø 100mm
- grey color - RAL 7035
- Includes: External electric louvre PAR 160 RAL7035, Plastic circular hose UK-PP 100/1000

400



10.2.A
10.2.B

Installation scheme




Bring fresh air into
your pool
and warm it with
the dehumidifier.



Our Innovation: **FRESH AIR SUPPLY**

Each Microwell dehumidifier has fresh air supply possibility. The air inlet is located under the condenser, that way the incoming fresh air is effectively heated at no cost thanks to heat recovery.



Fresh air metal extension for connection to dehumidifier



Plastic circular hose



Plastic external louver

Compatibility to All DRY range.



ADDITIONAL VENTILATION

Saving energy,
time & money

LET'S CONNECT AND EXPLORE TOGETHER!


Join our community and be the first to know about our latest updates, exclusive offers, and behind-the-scenes moments. We love sharing insights, tips, and exciting news with you!



Facebook




Instagram



LinkedIn



YouTube



TikTok



MICROWELL, spol. s r.o.

SNP 2018/42, 927 01 Šal'a, SLOVAKIA
p (+421) 31/770 7082
m (+421) 911/413 990
e export@microwell.sk

www.microwell.eu



Branch office PRAHA

Hlavní 1195
251 68 Hlubočinka - Sulice, CZ
m (+420) 773 621 599
m (+420) 608 855 364
e paha@microwell.cz
www.microwell.cz

Branch office BRNO

Pražáková 66
639 00 Brno, CZ
p (+420) 549 257 241
m (+420) 608 855 364
e brno@microwell.cz
www.microwell.cz

Branch office OSTRAVA

Slévárenská 411/12
709 00 Ostrava, CZ
p (+420) 596 638 227
m (+420) 608 855 364
e ostrava@microwell.cz
www.microwell.cz

Branch office BUDAPEST

Attila út 4.
1013 Budapest, HU
m (+36) 30 875 58 51
e microwell@microwell.hu
www.microwell.hu

Manufacturer reserves the right to change the technical and visual parameters without notice.



MICROWELL